

LIQUID CRYSTAL DISPLAY DEVICE HAVING A FRONT LIGHT UNIT

5

BACKGROUND OF THE INVENTION

(a) Field of the Invention

The present invention relates to a liquid crystal display (LCD) device having a front light unit as a light source. The present invention also relates to a structure of a new electroluminescent device.

(b) Description of the Related Art

Reflection type LCD devices are generally used in portable apparatus such as mobile telephones, personal data assistants, mobile computers and the like. The reflection type LCD device includes a front light unit as a light source and is described in Japanese Patent Laid-Open Publication Nos. 2000-29008, 2000-19330 and 11-326903. The conventional reflection type LCD device having a front light unit is described below, with reference to the configuration described in the Publication No. 2000-29008 as an example.

The conventional reflection type LCD device having a front light unit includes a LCD unit 120 and a front light unit 110, which are stacked together so that the front light unit 110 is disposed in front of the LCD unit 120, as shown in Fig. 1. The front light unit 110 includes a cold cathode tube or a linear array of light emitting diodes,

and is positioned in the vicinity of the edge of a light guide plate (layer) 112. Moreover, in this particular example, the front surface of the light guide plate 112 far from the LCD unit 120 has an inclined and stepped configuration, and a protective member 113 is disposed
 5 on top of the inclined and stepped surface.

The operation of the conventional LCD device is as follows. The light emitted from the light source 111 penetrates through a side surface 112a of the light guide plate 112, and following a variation in the course thereof at the reflective surface 112b, is transmitted through
 10 a light exit surface 112c and irradiated onto the LCD unit 120. The light irradiated onto the LCD unit 120 passes sequentially through a polarizing plate 126, a phase plate 125, a transparent substrate 124 and a liquid crystal layer 123, and is then reflected by a plurality of reflective members 122. The reflected light passes through the same
 15 members in a reverse direction, and is transmitted from the LCD unit 120 to the front light unit 110.

The amount of light transmitted from the upper surface of the reflective members 122 of the LCD unit 120 is controlled by the alignment direction of the liquid crystal molecules of the LC layer 123.
 20 Consequently, by controlling the voltage applied to the liquid crystal layer 123 separately for each of the reflective members 122, any desired pattern can be displayed by the LCD device.

The light from the LCD unit 120 is transmitted through the front light unit 110 toward the front side of the LCD device and
 25 reaches a viewer (not shown in the figure). In the configuration shown

in Fig. 1, damage to the reflective surface 112b is prevented by the protective member 113.

Referring to Figs. 20A and 20B, there is shown a cellular phone including the conventional reflection type LCD device having a front light unit. The cellular phone includes a first housing member 150 and second housing member 160, which are coupled to form a housing. The housing receives therein a LCD device 131, surface-mounted electronic parts 132, switch 136, speaker etc., which are mounted on a printed circuit board 130. Other parts 134 such as a vibrator and connectors are mounted on a flexible printed circuit board 133 and connected to the parts on the printed circuit board 130. A protective cover 161 is attached on the second housing member 160, for protecting the LCD device 131 against mechanical impact, moisture and stain. The protective cover 161 is made of a plastic material such as polycarbonate having a thickness of 1 mm. It is desired that the LCD device 131, especially if used in the cellular phone, have a smaller thickness .

The conventional reflection type LCD devices which utilize front light units are constructed so that light emitted from a light source positioned in the vicinity of the edge of a light guide plate is transmitted through the light guide plate, changes the course at the surface of the light guide plate, and then irradiates the reflection type LCD unit. Design of the mechanism for extracting the light from the light guide plate (such as a surface with a stepped or prism shaped configuration) is important, although it is difficult to ensure a uniform

brightness across the entire display area of the LCD device.

Furthermore, this type of mechanism for extracting light may also reflect and change the course of external light during a display operation in an ambient light condition wherein the front light unit is not used as a light source, and thus may cause a deterioration in the display performance. Moreover, if foreign matter such as dust or oil adheres to the surface of the light guide plate of the front light unit, then such soiled areas produce excessive scattering of the light, making a uniform brightness even more difficult. Furthermore, the light emitted from the light source also leaks out from the external side surface of the light guide plate outside the LCD device, thereby degrading the optical efficiency, or the efficiency of the light power.

Moreover, LCD devices are known which have a function for displaying information using only a portion of the display area (hereafter referred to as a "partial display function"), such as for time of day and communication status information on the display device of a mobile telephone. With the front light unit of the conventional LCD device, it is not possible to selectively irradiate a specified area of the display device.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a low cost reflection type LCD device equipped with a front light unit, which is capable of efficiently and uniformly illuminating a LCD unit and does not significantly degrade the display performance even with foreign

matter adhered thereto.

Another object of the present invention is to provide a low cost reflection type LCD device having a partial display function.

A further object of the present invention is to provide a method
5 for manufacturing a LCD device including a front light unit and having a simple structure.

A further r object of the present invention is to provide a small-size light unit implemented by an organic EL device.

In a first aspect of the present invention, a liquid crystal display
10 (LCD) device includes a LCD unit and a front light unit disposed at a front side of the LCD unit, the LCD unit having a plurality of light reflective members arranged in a matrix, the front light unit including
a light emission area for emitting light toward the LC unit and a transparent area for passing light reflected from light reflective
15 members of the LCD unit toward a front side of the front light unit.

In a second aspect of the present invention, a liquid crystal display (LCD) device includes a LCD unit and a front light unit
disposed at a front side of the LCD unit, the LCD unit having a plurality of light reflective members arranged in a matrix, the front
20 light unit including a transparent electrode, an electroluminescent layer and a non-transparent electrode consecutively arranged as viewed toward a front side of the front light unit.

In a third aspect of the present invention, an electroluminescence device includes a substrate and a multi-layered
25 structure including a transparent electrode, an electroluminescent layer

and a non-transparent electrode, which are consecutively formed on the substrate, wherein the non-transparent electrode has a patterned structure.

In a fourth aspect of the present invention, a method for manufacturing a liquid crystal display (LCD) device including the steps of forming a LCD unit having a plurality of reflective members arrayed in a matrix, forming a transparent electrode in front of the LCD unit, forming an electroluminescent (EL) layer on the transparent electrode, and forming a non-transparent electrode on the EL layer and having a specified pattern.

In a fifth aspect of the present invention, a method for manufacturing a liquid crystal display (LCD) device including the steps of forming a non-transparent electrode having a specific pattern on a transparent protective member, forming an electroluminescent (EL) layer on the non-transparent electrode, forming a transparent electrode on the EL layer, and forming a LCD unit at a rear side of the transparent electrode.

In accordance with the LCD devices of the present invention, and LCD devices manufactured by the methods of the present invention, the specified structures of the front light unit effectively function as front light units for the LCD units.

In accordance with the EL device of the present invention, the new structure of the EL device can be used for a variety of purposes such as a lighting unit.

The above and other objects, features and advantages of the

present invention will be more apparent from the following description, referring to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a schematic sectional view showing a conventional LCD device having a front light unit.

Figs. 2A is a developed perspective view of a LCD device having a front light unit according to a first embodiment of the present invention, and Fig. 2B is a schematic sectional view of the LCD device of Fig. 2A;

Fig. 3 is an explanatory diagram showing the positional relationship between a non-transparent electrode of a front light unit and a color filter of the LCD device of Fig. 2A;

Fig. 4 is an explanatory diagram showing the shape of the non-transparent electrode of the front light unit of the LCD device of Fig. 2A;

Fig. 5 is a perspective view showing a schematic configuration of a portion of the front light unit of the LCD device of Fig. 2A, as well as the operation of the front light unit;

20 Fig. 6 is a schematic cross-sectional view showing a modification of the front light unit of the LCD device of Fig. 2A;

Fig. 7 is a schematic cross-sectional view showing another modification of the front light unit of the LCD device Fig. 2A;

Fig. 8 is a schematic cross-sectional view showing still another modification of the front light unit of the LCD device of Fig. 2A;

Fig. 9 is an explanatory diagram showing a modification of the aforementioned LCD device;

Fig. 10 is an explanatory diagram showing a modification of the non-transparent electrode of the front light unit of the LCD device
5 of Fig. 2A;

Fig. 11 is an explanatory diagram showing the configuration of a non-transparent electrode of a front light unit, in a LCD device with a front light unit according to a second embodiment of the present invention; and

Fig. 12 is an explanatory diagram showing the configuration of a non-transparent electrode of a front light unit, in a LCD device of
10 Fig. 11.

Fig. 13 is a sectional view of a LCD device according to a third embodiment of the present invention.

Fig. 14 is a detailed sectional view of the LCD device of Fig.
15 13.

Fig. 15 is a flowchart of a process for manufacturing a LCD device of Fig. 13.

Fig. 16 is a sectional view of a LCD device according to a third
20 embodiment of the present invention.

Fig. 17 is a sectional view of a LCD device according to a fourth embodiment of the present invention.

Fig. 18 is a detailed sectional view of the LCD device of Fig.
17.

Fig. 19A is a sectional view of an organic EL device according
25

to a fifth embodiment of the present invention, and Fig. 19B is a perspective view showing the usage of the organic EL device of Fig. 19A.

Figs. 20A and 20B are top plan view and a sectional view,
5 respectively, of a conventional cellular phone.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Embodiments of the present invention will be described in
10 detail, with reference to the accompanying drawings, wherein similar constituent elements are designated by similar or related reference numerals throughout the drawings.

Fig. 2A shows the principal constituent elements of the LCD
device according to a first embodiment of the present invention, and
15 Fig. 2B shows the configuration of those elements. In the LCD device of the present embodiment, as shown in Fig. 2A, a front light unit 10 is stacked onto a LCD unit 20 at the front surface thereof. As can be seen in the sectional view of Fig. 2B, the front light unit 10 includes a transparent electrode 12, an electroluminescence (EL) layer
20 13 formed of an organic material, and a non-transparent electrode 14, which are layered consecutively onto a transparent substrate 11. A protective layer 15 is provided on the front surface of the front light unit 10.

The LCD unit 20 includes: a transparent substrate 21 mounting
25 thereon a plurality of reflective members 22 arranged in a matrix and

an alignment film 23; a transparent substrate 27 mounting thereon a plurality of color filters 26 and an alignment film 25; and a liquid crystal layer 24 disposed between the transparent substrate 21 and the transparent substrate 27.

Fig. 3 depicts the positional relationship between the non-transparent electrode 14 of the front light unit 10, and the color filters 26 of the LCD unit 20, which are viewed from the front of the LCD device. The non-transparent electrode 14 of the front light unit 10 is formed in a mesh structure as shown in Fig. 4, and includes an external terminal 14A for applying a driving voltage. In the example shown in Fig. 3, a single square of the mesh of the non-transparent electrode 14 of the front light unit 10 is formed so as to correspond to four pixels of the LCD unit 20 each including R, G, B color filters or reflection members. The proportion of the area occupied by the non-transparent electrode 14 is extremely small relative to the front surface of the front light unit 10. The area of the non-transparent electrode 14 as viewed from the front of the LCD device corresponds to a luminescence area or light emission area of the organic EL layer 13, and the other area of the organic EL layer 13 not covered by the non-transparent electrode 14 constitutes a light transmission area. The luminescence area and the light transmission area are disposed alternately in the organic EL layer 13 in X- and Y- directions.

Fig. 5 shows the configuration of the front light unit 10 in the vicinity of the external terminals for applying a source voltage to the electrodes including the non-transparent electrode 14 and the

transparent electrode 12 of the front light unit 10. The transparent electrode 12 is entirely formed across the surface of the transparent substrate 11, and with the exception of a terminal section thereof, is covered completely by the organic EL layer 13 which also functions as an insulating layer.

The mesh shaped non-transparent electrode 14 formed on top of the organic EL layer 13 does not contact the transparent electrode 12. The front light unit 10 and the LCD unit 20 may be arranged with an air gap disposed therebetween, or may be fixed together using a transparent adhesive having a refractive index approximately equal to that of the transparent substrate.

As follows is a more detailed description of the present embodiment, including specific examples of materials, manufacturing processes and numerical values. The transparent substrate 11 of the front light unit 10 is a glass plate, plastic substrate, film substrate or the like, having a thickness of approximately 0.3 to 1 mm. The transparent electrode 12 is formed by sputtering indium tin oxide (ITO), for example, across the entire surface of the transparent substrate 11. If ITO is used as a material for the transparent electrode 11, the sheet resistance is approximately $20 \Omega/\square$ and the thickness is approximately 100 nm. Known examples of the structure for the organic EL layer 13 include a two-layered structure including a luminescence layer and a hole injection/transport layer, a three-layered structure including an additional electron injection/transport layer to the two-layered structure, and another

structure incorporating therein an additional thin insulating film formed at the interface with the metallic electrode in the two- or three-layered structure. Any of these structures can be applied to the configuration shown in Fig. 2B.

5 In other words, although Fig. 2B schematically depicts the organic EL layer 13 as a single layer, a variety of constructions, such as those described above, are possible. Known methods of manufacturing the organic EL layer 13 include spin-coating, vacuum evaporation and ink jet printing. Depending on the manufacturing
10 method used, the manufacturing conditions employed are determined, such as selection of the organic EL material, including whether a high molecular weight or low molecular weight organic EL material is used, the structure of the underlying substrate or base, and the method used for manufacturing the upper electrode.

15 The organic EL layer 13 of the present embodiment is formed as follows. Examples of the material for a hole injection/transport layer include a triarylamine derivative, an oxadiazole derivative, and a porphyrin derivative. Examples of the material for a luminescent material include a metal complex of either 8-hydroxyquinoline or a
20 derivative thereof, a tetraphenylbutadiene derivative, and a distyrylaryl derivative. These layers may be formed by using a vacuum evaporation technique to form a multi-layered structure each layer of which is approximately 50 nm thick. During this process, a metallic shadow mask is used so that the organic EL material is not
25 deposited on the terminal section of the transparent electrode 12

shown in Fig. 4. The wavelength of light can be selected by appropriate selection of the organic EL material. In this embodiment, the material for the organic EL layer 13 is selected so that the light has three components with peaks at approximately 450 nm, 540 nm and 630 nm corresponding to the three primary colors.

The non-transparent electrode 14 is formed, for example, by vacuum evaporation of a material such as an alloy of aluminum and lithium through a metallic shadow mask, to yield a layer approximately 200 nm thick. Finally, in order to protect the organic EL layer 13 against oxygen and moisture, a protective layer 15 made of a metallic oxide, or a metallic sulfide or the like is provided over the entire surface. Alternatively, instead of forming the protective layer 15, a package structure may also be formed by covering all the elements with a plastic cover, and then replacing the air inside the plastic cover with an inert gas such as nitrogen or argon.

By applying a source voltage to the light emission area of the organic EL layer 13 sandwiched between the transparent electrode 12 and the stripe sections of the non-transparent electrode 14, with the transparent electrode 12 functioning as the anode and the non-transparent electrode 14 as the cathode, the organic EL layer 13 functions as a white light emitting diode with three light emission peaks.

The LCD unit 20 may be any one of a variety of reflection type LCD devices, which differ in terms of the system used for writing image signals to the pixels. Suitable LCD units include simple

matrix type units in which the orientation of the liquid crystal molecules of the LC layer is controlled by stripe electrodes orthogonal with each other, MIM (metal-Insulator-Metal) type units in which a voltage is applied to separate pixel electrodes by using a diode element having an insulator sandwiched between two layers of a metal, and TFT type units in which instead of the aforementioned diode, a thin film transistor (TFT) with a base material such as amorphous silicon or polycrystalline silicon is used for applying a voltage to separate pixel electrodes. In any of these types, the area of the liquid crystal layer for which the voltage can be separately controlled includes a plurality of pixel electrodes, and these pixel electrodes are arrayed in a suitable order.

The LCD unit 20 shown in Figs. 2A and 2B is an example of the reflection type color LCD unit. The color LCD unit 20 includes the electrode substrate 21 having a plurality of reflective members arrayed regularly on top of a glass substrate or the like, and the transparent substrate 27 having a uniform transparent electrode 27 and a separate color filters 26, with the liquid crystal layer 24 having a thickness of 2 to 5 μm being disposed therebetween. The transparent substrate 27 and the electrode substrate 21 are positioned so that the color filters 26 and the reflective members 22 are aligned in a one-to-one correspondence. Furthermore, the alignment films 23 and 25 are formed on those surfaces of the two substrates 27 and 21 in contact with the liquid crystal, and cause the liquid crystal molecules to be oriented at a specific angle.

Moreover, a phase plate 28 and a polarizing plate 29 are layered onto the surface of the transparent substrate 27 far from the liquid crystal 24. The reflective members 22 have a corrugated shape so as to reflect the light across a wide range of directions. A plurality of drive voltages can be applied to separate reflective members 22. These reflective members 22 can be formed by, for example, using photolithography to form a corrugated shape on a material such as polyimide, using a sputtering technique to form a layer of a highly reflective material such as aluminum thereon, and then using photolithography to form separate patterns. Each pixel, which is the unit element for display in the LCD device, includes three color filters R, G, B in a single unit element.

If the pitch of the arrangement of these pixels in the array is small, then a high definition image display is possible. For example, it is assumed that each of R, G, B pixels shown in Fig. 3 occupies an area of approximately $120\ \mu\text{m} \times 30\ \mu\text{m}$, and is arrayed at a pitch of $127\ \mu\text{m}$. In addition, the thickness of the transparent substrate 27 is between 0.3 mm and 1 mm. In such a case, as will be understood from Fig. 3, the non-transparent electrode 14 of the front light unit 10 is formed as a mesh having a pitch equivalent to two pixels of the LCD unit 20, namely $254\ \mu\text{m}$. If the pattern width of the stripes of the mesh is set at $10\ \mu\text{m}$, then the proportion of the surface area occupied by the non-transparent electrode is $(10/254) \times (10/254) = 0.00155$, equivalent to a 99.8% transparency.

Next is a description of the operation of the LCD device of the

first embodiment with reference to Fig. 2A to Fig. 5. If a voltage of approximately 5 V to 15 V is applied between the transparent electrode 12 and the non-transparent electrode 14 in the front light unit 10, then a white light is emitted from the light emission area of the organic EL layer 13 sandwiched between the mesh of the non-transparent electrode 14 and the transparent electrode 13. If no particular modifications or alterations are made to the construction of the organic EL layer, then the light is emitted equally in all directions. As will be understood from Figs. 2A, 2B and 5, the LCD unit 20 is irradiated by the light emitted in the direction toward the LCD unit 20 as it is emitted, as well as by the light emitted toward the non-transparent electrode 14 after the reflection thereof at the rear surface of the non-transparent electrode 14.

The light passes sequentially through the transparent electrode 27 and the color filters 26 of the LCD unit 20, with only the light components each having the wavelength selected by a corresponding one of the color filters 26, reaching the reflective members 22. The positional relationship between the non-transparent electrode 14 (namely, the light emission area) and the reflective members 22 determines whether or not the surfaces of the reflective members 22 are irradiated uniformly. A larger pitch of the light emission area, i.e., larger pitch of the mesh, affords a less uniform distribution of brightness across the surface including the reflective members 22. In contrast, a smaller pitch of the mesh affords a larger area of the non-transparent electrode relative to the entire surface area.

It is to be noted that, if the front light unit 10 is not energized, then the amount of light reaching the reflective members 22 decreases, resulting in a dimming of the screen or image. In this manner, it is necessary to consider both the efficiency of usage of the surrounding light and the brightness distribution resulting from the front light unit 10 before determining the positional relationship between the non-transparent electrode 14 and the reflective members 22. This type of consideration produces the positional relationship between the mesh-shaped non-transparent electrode (namely, the light emission area) 14 and the reflective members 22 (and color filters 26) such as shown in Fig. 3, where four pixels are formed corresponding to each square of the mesh.

Furthermore, since the distance from the light emission area of the front light unit 10 to the reflective members 22 of the LCD unit 20 is as large as 0.6 mm, and the directivity of the light is not narrow, as described before, the reflective members 22 are irradiated uniformly. The targeted amount of the surrounding light used, and the amount of the light emitted from the front light unit are dependent on the design, e.g., the environment in which the LCD device is to be used. The numerical values described above are mere examples, and do not limit the structure of the LCD device of the present invention.

The light reaching the reflective members 22 is reflected and passes back through the liquid crystal layer 24 and the color filters 26 in sequence. The light, after passing through the area not occupied by the non-transparent electrode 14 of the front light unit 10, ultimately

reaches a viewer (not shown in the figures). The amount of light transmitted can be controlled by changing the voltage applied to the liquid crystal layer 24, thereby enabling the display of any desired image.

5 As described above, in the LCD device of the present embodiment, because the front light unit 10 is of an area-emission type and has a light emission area and a transparent area disposed alternately in a suitable configuration, an excellent display performance can be obtained both when the front light unit is used as
10 a light source, and when the light source in the front light unit is not used. In particular, when the front light unit is used to emit light, the light can be irradiated uniformly over the entire display area of the LCD device.

15 Furthermore, since no special mechanism is used for changing the course of external light entering from the surroundings, the problems associated with conventional LCD devices having front light units are not involved in the present embodiment. Namely, the scattering of surrounding external light and the deterioration in display performance, when foreign matter such as dust or oil adheres to the
20 display surface, can be resolved. Moreover, since almost all the light emitted from the front light unit is used for the brightness of the LCD device, and almost all of the reflected light reaches the viewer, the present embodiment offers the advantage of a high optical efficiency when the front light unit is used.

25 In the above description, the non-transparent electrode 14 is

made of a single material; however, it is also possible to form a non-transparent electrode 14 in which the surface not in contact with the organic EL layer 13 has a light absorption property, by for example, anodizing the surface of an aluminum sheet and plating a black colored pigment thereon. In such a case, the light which enters the front light unit from the surroundings and does not permeate through the front light unit is absorbed by the non-transparent electrode. Consequently, reduction in the contrast ratio of the LCD device resulting from the reflection by the non-transparent electrode is prevented, and a high level of contrast ratio can be achieved.

In the above embodiment, a front light unit is described in which only the non-transparent electrode is patterned and formed into a mesh shape, with the exception of the terminal section thereof. However, the present invention does not limit the structural elements to the particular shape. In other words, similar effects can be achieved if, for example, other structural elements of the front light unit such as the organic EL layer and the transparent electrode are patterned in a similar manner.

Fig. 6 to Fig. 8 are schematic sectional views showing modifications of the front light unit of the first embodiment.

In a front light unit 10b shown in Fig. 6, an organic EL layer 13b is patterned similarly to a non-transparent electrode 14b, and is positioned beneath the non-transparent electrode 14b. In a front light unit 10c shown in Fig. 7, a transparent electrode 12c is patterned and is positioned beneath a non-transparent electrode 14c with an

intervention of an organic EL layer 13c. In a front light unit 10d shown in Fig. 8, both a transparent electrode 12d and an organic EL layer 13d are patterned, and are positioned beneath a non-transparent electrode 14d. The operation and effects of these front light units are similar to those described for the embodiment of Fig. 2A.

It is to be noted, however, that the modification shown in Fig. 8 is different from the other modifications and the embodiment in that the organic EL layer 13d is covered by the non-transparent electrode 14d on the side surfaces thereof, and thus light escaping through the side surfaces is blocked by the non-transparent electrode 14d. In the modifications shown in Fig. 6 to Fig. 8, additional process steps are conducted for patterning the electrode materials for the front light unit by using photolithography. These additional process steps are associated with an undesirable increase in the manufacturing costs, although the modifications of Fig. 7 and Fig. 8 offer the advantage of improving the optical efficiency of the front light unit, by removing the overlapping with the transparent electrode at the terminal section.

In contrast, in the configuration shown in Fig. 5, since the organic EL layer 13 and the transparent electrode 12 also exist beneath the terminal section formed by patterning of the non-transparent electrode 14, light emission also occurs from this terminal section. However, the terminals are formed in an area of the LCD unit 20 where no reflective members 22 exist, and thus the light emitted from the terminal section cannot be utilized for display purposes.

Nevertheless, this light could be used for display other than the LCD,

unit or for external illumination.

In the above embodiments, examples are described in which the mesh-shaped light emitting area of the front light unit 10 is positioned in alignment with the space or gap between the reflective members 22 of the LCD unit 20. An example of a conceivable modification of the first embodiment is shown in Figs. 9A and 9B, where a mesh shaped non-transparent electrode of a front light unit 10e is positioned at a 45-degree rotation relative to the directions of the arrangement of the reflective members in the LCD unit 20. In the first embodiment, if a stripe of the non-transparent electrode 14 overlaps with the columns of the reflecting members 22 displaying a particular color, the brightness of the particular color is affected by the overlapping, thereby resulting in a decrease in the particular color. The purpose of the rotation of the mesh of the non-transparent electrode 14 shown in Figs. 9A and 9B is to prevent such a situation. Both angles need not be limited to 45 degrees. However, depending on the selection of factors such as these angles and the pitch of the non-transparent electrode 14, a moire pattern may occur, causing a deterioration in the display performance of the LCD device, and so care must be taken in consideration thereof.

Generally, when a pattern of one period is superposed on a pattern with a different period, an undesirable regular pattern (moire pattern) occurs, and its period is determined by the two periods.

When a front light unit of the conventional structure is stacked onto a LCD unit, this type of moire pattern can develop as a result of the

regular pattern provided on the light guide plate and the regular pattern of the structural elements of the LCD unit. In the aforementioned Japanese patent laid-open publications relating to conventional technology, conditions relating to the structural elements are determined experimentally so that moire patterns are suppressed to an allowable level to the viewer.

Specifically, the results in a requirement whereby the angle between the one-dimensional pattern provided on the light guide plate and the pixel array of the LCD unit should be between 22.5 and 25 degrees. This numerical range is characteristic only at specific experimental conditions, and is in no way widely applicable. For example, the angle varies depending on experimental factors such as the viewing angle and the brightness of the surroundings.

In contrast, it is already known that one method of preventing the formation of a moire pattern is to ensure that the spatial frequency of one pattern is an integral multiple of the spatial frequency of the other pattern. The configuration shown in Fig. 3 satisfies this requirement in that the period of one pattern is set at twice the period of the other pattern, and consequently, substantially no moire pattern occurs.

If the mesh pattern is inclined at an angle of 45 degrees, as described above, then the spatial frequency spectrum of the mesh pattern projected in the direction of the regular pattern of the LCD device has no sharp peaks, and as a result, any moire pattern is practically unnoticeable.

In addition, the description is made on a front light unit having non-transparent electrodes which are mesh shaped. However, the shape of the non-transparent electrode is not limited to this type, or a mesh shape. For example, similar effects can be achieved using the linear patterns extending parallel to one another, as shown in Fig. 10, or interlocking patterns with zigzag lines, such as shown in Fig. 11.

Furthermore, in the above description, a reflection type LCD unit having color filters is described as an example,. The present invention can also be applied to monochrome reflection type LCD devices without a color filter. Moreover, the front light unit described in the example has a construction in which light is irradiated towards a transparent substrate; however, an alternative construction is also possible in which the transparent electrode and the non-transparent electrode are interchanged and the light is irradiated away from the transparent substrate. In this manner, it will be understood that various modifications of the constituent elements are possible without departing from the present invention, and thus such modifications are viewed as variants of the first embodiment.

In a second embodiment of the present invention, the non-transparent electrode of the front light unit has a divided configuration. More specifically, Fig. 11 is an explanatory diagram showing the configuration of such an electrode of the front light unit. In Fig. 11, the non-transparent electrode of the front light unit is divided into three sections. The second embodiment is different from the first embodiment in the configuration wherein a specified voltage is

applied independently to any number of these three sections. By enabling the specified voltage to be applied independently to three parallel electrodes, the electrode configuration of Fig. 11 enables the brightness of the front light unit to be set in three steps.

5 This offers the advantage that the brightness of the front light unit can be controlled by a simple drive circuit. Even in the configuration of the first embodiment, the brightness of the front light unit can be controlled by adjusting the voltage applied to the organic EL layer. However, this requires an accurate understanding of the
10 characteristics of the voltage applied to, and the light output from, the organic EL layer, and also requires a precise control for the voltage to be applied. In the configuration of Fig. 11, three digital signals enable eight different brightness levels to be achieved, corresponding to the eight possible combinations of application of a single voltage,
15 for example 5 V, wherein the single voltage is applied to any number of the three electrodes having different configurations. By using this type of digitized drive, an advanced amplifier circuit is unnecessary. It is to be noted that increase of the number of electrodes enables a more precise brightness control to be achieved.

20 In the examples described above, the non-transparent electrode of the front light unit is divided into a plurality of sections. Similar effects can be achieved by dividing the transparent electrode into a plurality of sections. Consequently, such modified configurations are viewed as variants of the second embodiment of the present invention.

25 In the second embodiment, all of the plurality of divided

electrodes in the front light unit cover substantially the entire display area of the LCD device. In an alternative, a configuration such as shown in Fig. 12 may be used, wherein the non-transparent electrode of the front light unit is divided into two sections which cover separate display areas of the LCD device. Such a configuration offers the advantage of enabling illumination of only a specific minor area of the LCD device. A partial display function of mobile telephones is an example of this type of display technique.

In the example described above, the non-transparent electrode of the front light unit is divided into a plurality of sections. Similar effects can be achieved by dividing the transparent electrode into a plurality of sections. Consequently, such modified configurations are viewed as variants of the second embodiment of the present invention.

Referring to Fig. 13, a LCD device according to a third embodiment of the present invention includes a front light unit having a smaller thickness. Specifically, the front light unit 40 is formed on the display panel of the LCD unit 20, and a protective member or cover 50 is disposed in front of the front light unit 40. The protective cover 50 is fixed onto the front light unit 40 by an adhesive at the outer periphery of the front light unit 40, i.e., outside the display area of the LCD device. The space 60 between the front light unit 20 and the protective cover 50 is filled with an inert gas, such as nitrogen. The LCD device including the LCD unit 20, front light unit 40 and the protective cover 50 is fixed to a housing 70 of a cellular phone, for example.

Referring to Fig. 14, there is shown a detailed configuration of a portion of the LCD device of Fig. 13. The front light unit 40 has a multi-layered structure including a transparent electrode 42, an organic EL layer 43, a non-transparent electrode 44, the non-transparent electrode 44 having a smaller area compared to the transparent electrode 42 and the organic EL layer 43.

The LCD unit 20 includes an electrode substrate 21 made of glass and mounting thereon a plurality of reflective members 22 arrayed in a matrix, a transparent substrate 27 mounting thereon a transparent electrode having a uniform thickness and a plurality of color filters 26, and a LC layer 24 sandwiched between the electrode substrate 21 and the transparent substrate 27. The LC layer 24 has a thickness of 2 to 5 μ m. The transparent substrate 27 and the electrode substrate 21 are aligned so that the color filters 26 and the reflective members 22 oppose in one-to-one correspondence. Alignment films 23 and 25 are formed on the surfaces of both the substrates 21 and 27, respectively, for alignment of LC molecules in the LC layer 24 with a specified orientation.

Examples of the LCD unit 20 used in the LCD device of the present invention include a variety of types of LCD unit, such as a simple matrix type wherein the orientation of the LC molecules is controlled by a pair of groups of stripe electrodes, each group extending normal to the other group, a metal-insulator-metal (MIM) type wherein a plurality of diodes each having a MIM structure apply voltages to respective pixel electrodes, a TFT type wherein a plurality

of thin film transistors having a base material of polysilicon apply voltages to respective pixel electrodes. In either type, a plurality of pixel electrodes arranged in a matrix and each controlled independently from another applies a voltage to one of a plurality
 5 areas of the LC layer.

The LCD device of the present embodiment is fabricated by the process shown in Fig. 15. In general, the LCD unit 20 has a polarizing plate 29 made of a polymer at the front side thereof. In the fabrication process, a transparent buffer layer 41 is formed on the polarizing plate
 10 29 of the LCD unit 20 in step S1. The transparent buffer layer 41 protects the polarizing plate 29 against damages caused by an organic solvent.

ITO (indium-tin-oxide) is then sputtered onto the entire surface of the transparent buffer layer 41 to form a transparent electrode 42 in
 15 step S2. In this step, care is taken for the heat generated during the sputtering step not to damage the constituent elements of the LCD device such as the polarizing plate 29. ITO is especially suited as the material for this purpose because the ITO film formed even at the room temperature has a uniform thickness and a relatively lower
 20 electric resistance. It is preferable that the transparent electrode 42 made of ITO film has a sheet resistance of $20\ \Omega/\square$ and a thickness of 100 nm.

Organic EL materials are then deposited on the transparent electrode 42 by using a vacuum evaporation technique to form an
 25 organic EL layer 43. The organic EL layer 43 may have any of known

structures such as a two-layer structure including a luminescence layer and a hole injection/transport layer, or a three-layer structure including an electron injection/transport layer in addition to the two layers as recited above. A thin insulator film may be provided at the interface
5 between the organic EL layer and the metallic electrode. Although the organic EL layer 43 is depicted as a single layer in Fig. 14, the organic EL layer may have one of such structures.

The organic EL layer 43 may be formed by a spin-coating technique, vacuum evaporation technique, or ink jet printing technique,
10 and the organic EL materials, structure of the base and the process for forming the top electrode are selected depending on the technique used therein.

In the organic EL layer 43 of the present embodiment, the material for a hole injection/transport layer may be selected from the group including triarylamine derivative, an oxadiazole derivative, and
15 a porphyrin derivative. The material for a luminescent layer may be selected from the group including a metal complex of either 8-hydroxyquinoline or a derivative thereof, a tetraphenylbutadiene derivative, and a distyrylaryl derivative. These layers may be formed
20 by using a vacuum evaporation technique to form a multi-layered structure each layer of which is approximately 50 nm thick. The wavelength of light can be selected by appropriate selection of the organic EL material. In this embodiment, the material for the organic EL layer 43 is selected so that the light has three components having
25 three peaks at approximately 450 nm, 540 nm and 630 nm in the

wavelength corresponding to the three primary colors.

Subsequently, an alloy such as aluminum-lithium alloy is vacuum-evaporated by using a metallic shadow mask to form a non-transparent electrode 44 in step S4. The non-transparent electrode 44 has a thickness of 200 nm, for example.

A transparent protective cover 50 is then attached for protecting the front light unit 40 including the non-transparent electrode 44 etc. against oxygen or moisture and also protecting the LCD device against an external mechanical impact. The protective cover 50 has a thickness of about 1 mm and encloses the LCD device as a whole, and the air inside the protective cover 50 is replaced with an inert gas such as nitrogen or argon in step S5. The space within the protective cover 50 depends on the mechanical accuracy of the constituent elements of the LCD device, and may be around 0.3 mm for a LCD device having a diagonal size of 2 to 4 inches.

The process steps from the formation of the organic EL layer to the replacement by the inert gas is preferably conducted so that the constituent elements are not exposed to air. This is achieved by using a plurality of vacuum reactors suited for sputtering, evaporation etc.

In the LCD device thus fabricated, by applying a voltage between the electrodes 41 and 43, with the transparent electrode 41 being an anode and the non-transparent electrode 44 being a cathode, the area of the organic EL layer 43 sandwiched between the transparent electrode 41 and a stripe of the non-transparent electrode 44 functions as a diode emitting white light with three emission peaks.

The structure wherein the front light unit 40 is formed directly on the front surface of the LCD unit 20 affords an overall thickness smaller than the LCD device of Fig. 2 by the thickness of the transparent substrate. In addition, if the LCD device of the present embodiment is mounted on a cellular phone, the protective cover 50 may be implemented by a portion of the housing of the cellular phone. This reduces the number of steps for the assembly of the cellular phone.

The front light unit 40 has light emission areas and transparent areas alternately arranged and functions as an area-mission light source, as in the case of other embodiments. Thus, irrespective of whether or not the front light unit 40 is used as a light source for the LCD unit, the LCD device has an excellent display performance. More specifically, if the front light unit is used as a light source, the front light unit 40 illuminates uniformly over the entire display area of the LCD unit 20. Since there is no specific mechanism for changing the direction of external light in the front light unit 40, the LCD device of the present embodiment solves the problem of scattering of light or degradation of the display performance due to attachment of foreign matter, as encountered in the conventional LCD device. Furthermore, since almost all of the light emitted by the front light unit 40 is used as illumination of the LCD unit 20 and reflected by the LCD unit 20 to reach the viewer, the optical efficiency of the front light unit 40 can be improved.

In operation of the LCD device of Figs. 13 and 14, a voltage of

5 to 15 volts is applied between the transparent electrode 42 and the non-transparent electrode 44 of the front light unit 40, whereby white light is emitted from the emission area of the organic EL layer 43. If the front light unit 40 has no specific structure for light reflection or refraction, white light is emitted in all the directions. Thus, the light emitted toward the LCD unit 20 is irradiated as it is, whereas the light emitted toward the non-transparent electrode 44 is reflected thereby and also irradiated to the LCD unit 20. The light passes by the transparent substrate 27 and the color filters 26 of the LCD unit 20, and the light components having wavelengths selected by the color filters 26 reach the reflective members 22. The light components reflected by the reflective members 22 pass by the LCD unit 20 and the transparent area of the front light unit 40, thereby reaching the viewer. The light components have image information based on the control of voltages applied to the pixel elements of the LCD layer 24.

If there is a possibility that the protective cover 50 does not afford a sufficient protective function against oxygen or moisture, then, as shown in Fig. 16, a moisture absorbent 61 such as barium oxide may be used in the space 60 to which the front light unit 40 is exposed.

In Fig. 16, the moisture absorbent 61 is received in a depression formed in the inner wall of the protective cover 50, and is fixed by a membrane 62. The moisture absorbent 61 is typically granular and has a grain size of about 0.2 mm. Thus, 0.3 mm is sufficient for the depth of the depression. This structure prevents an increase of the overall thickness of the LCD device.

Referring to Figs. 17 and 18, a LCD device according to a fourth embodiment of the present invention has a structure wherein the front light unit 40b is formed on the inner wall of the transparent protective cover 50b. More specifically, the front light unit 40b includes a patterned non-transparent electrode 44b, an organic EL layer 43b and a transparent electrode 42b, which are consecutively formed on the inner wall of the protective cover 50b. The LCD unit 20 is fixed by an adhesive to the protective cover 50b on which the front light unit 40b is formed. The space 60b between the front light unit 40b and the LCD unit 20 is filled with an inert gas such as nitrogen.

The operation of the LCD device of the present embodiment is similar to the operation of the LCD device of the third embodiment. The present embodiment achieves advantages similar to those of the third embodiment, In addition, due to the structure wherein the front light unit is formed directly on the protective cover, a moisture absorbent is unnecessary in the present embodiment, which enables further reduction of the overall thickness of the LCD device. The LCD device of the present invention is especially suited to the cellular phone such as shown in Figs. 20A and 20B.

According to the above embodiments of the present invention, the LCD devices can be irradiated uniformly and efficiently, resulting in a superior display performance. Furthermore, even the adherence of foreign matter to the surface of the front light unit has little effect on the display performance. In addition, the number of components is smaller compared to the conventional front light unit having a light

guide plate, enabling a reduction in manufacturing cost.

According to the second embodiment, in addition to the effects described above, the brightness of the front light unit can also be controlled by a simple drive circuit. According to the third
5 embodiment, in addition to the effects observed for the first embodiment, a reflection type LCD device with a partial display function is also produced at low cost.

Referring to Fig. 19A, an EL device according to a fifth
10 embodiment of the present invention includes the structure similar to the structures of the front light unit in the LCD device of the first embodiment. More specifically, the EL device generally designated by numeral 10 includes a transparent substrate 11, and a multi-layered structure formed thereon. The multi-layered structure includes a
15 transparent electrode 12, an organic EL layer 13, a patterned non-transparent electrode 14 and a protective layer 15, consecutively formed on the transparent substrate 11. The patterned non-transparent electrode 14 has a mesh structure.

In the EL device of the present embodiment, the front light unit includes a plurality of light emission areas each sandwiched between
20 the transparent electrode 12 and one of the stripes of the mesh of the non-transparent electrode, and a plurality of transparent areas alternately and regularly arranged with the light emission areas. The EL device is used in association with a LCD unit as a front light unit therefor.

25 Referring to Fig. 19B, the EL device 10 of the present

embodiment may be used as a lighting unit for illumination of a book or a newspaper, with the transparent substrate being disposed on a metallic plate or a reflector. The EL device has smaller dimensions compared to the conventional light used for this purpose.

5

Since the above embodiments are described only for examples, the present invention is not limited to the above embodiments and various modifications or alterations can be easily made therefrom by those skilled in the art without departing from the scope of the present invention.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
22